

CS-650 クランクストッパー適合自転車について

本商品のクランクストッパーの位置が、ご使用予定の自転車のサイズに合わない場合は本商品をご利用になることができません。

1. 【車種を確認してください】


- ・ 自転車ロードレーサー、クロスバイク、マウンテンバイク等のスポーツ自転車の使用を想定して設計されています。それ以外の車種ではご利用になれない場合がございます。
- ・ 折りたたみ自転車や電動アシスト自転車では、ご使用にならないでください。特殊なフレーム形状であったり、特殊な部品が付属している場合があるのでサポート対象外といたします。
- ・ 泥除け、スタンドなどがついており、直立させることが出来ない自転車は使用できません。
- ・ フリー機構が備わっていない（ペダルが逆回転しないもの）ピストについては使用できません。
- ・ 一部のマウンテンバイクの場合はサイズによっては、適合しない場合がございます。「2. ホイール及びタイヤサイズを確認してください」、「3. BB（ボトムブラケット）の位置を確認してください」をよくお読みになり、サイズをメジャーなどで採寸して下さい。
- ・ ホイールサイズが 20 インチ以上であれば小径車でも対応します。

2. 【タイヤ幅を確認してください】

- ・ タイヤ幅が 60mm 以上の自転車は使用できません。

3. 【BB（ボトムブラケット）の位置を確認してください】

- ・ 下図の※1の長さを採寸してください。



4. その他の影響する仕様

- ・ クランク長が 165mm 未満の自転車には対応しない場合があります。
- ・ チェーンリングが 54 T より大きい自転車には対応しない場合があります。
- ・ クランクシャフトが極端に太いものは対応しない場合があります。
- ・ ホイールベースが長い自転車には対応しない場合があります。
- ・ 左右のクランクの間隔が極端に広いものには対応しない場合があります。
- ・ 重量が 16kg を超える自転車ではご使用にならないでください。

Bicycles compatible with CS-650 Crank Stopper Stand

- ・ The product can not be used when the size of a bicycle is not suitable for the position of the crank stopper of the product.

1. 【Check the type of your bicycle】


- ・ The product has been designed assuming that it is used with the sports bikes, such as road bikes, cross bikes, and mountain bikes. You may not use it in other type of bicycles.
- ・ This product may not support a folding bicycle and electric assist bicycle, please do not use it. Because specific frame and parts may be attached, support is inapplicable.
- ・ This product may not support a bicycle having a mudguard or stand attached to its rear wheel, because the bicycle cannot be raised vertically.
- ・ This product may not support pist bikes with no ratchet wheel backstop mechanism attached to the rear wheel.
- ・ Some of mountain bikes may not be compatible with the product because of their sizes. Read also "2. Check the sizes of wheels and tires" and "3. Check the positions of bottom bracket (BB)" carefully, and measure the sizes.
- ・ It is compatible with small bicycles with wheels \geq 20 inch.

2. 【Check the sizes of wheels and tires】

- ・ Tire width cannot use the bicycle of more than 60mm.

3. 【Check the positions of bottom brackets (BB)】

- ・ Measure the distance indicated by an arrow as shown below.




4. Other specifications concerned:

- ・ This product may not support a bicycle having the crank < 165 mm in length.
- ・ This product may not support a bicycle having the chain ring > 54T.
- ・ This product may not support a bicycle having an extremely-thick crank shaft.
- ・ This product may not support a bicycle having a long wheelbase.
- ・ This product may not support a bicycle having the extremely-wide space left between the right and left cranks.
- ・ This product may not support a bicycle more than 16 kg in weight.

5. クランクストッパー及び支柱の高さについて

本商品は支柱中間部のジョイント部で高さ調整が出来ます。使用する自転車のクランク高さに合わせて調整してください。一番低くした場合、一番高くした場合は下記の高さとなります。

- ・クランクストッパーの高さの調整域は、床面からの高さが750mm-1000mmの範囲です。
- ・クランクストッパーから支柱上端まで535mmになります。



6. お問い合わせ

■株式会社サイクルロッカー

〒240-0113 神奈川県三浦郡葉山町長柄 1 7 TEL.046-877-0566

FAX.050-6861-7143


MAIL:info@cyclelocker.net

WEB http://cyclelocker.net

2016年9月 CS-650BK/CS-650WH/CS-650RD

5. about the height of the crank stopper and the pillar

- ・ This product can do height adjustment in a joint part of the pillar intermediate part. Please adjust it to the crank height of the bicycle to use. When I lower it most, or when I raise it most, it becomes the following height.
- ・ In the adjustment area of the height of the crank stopper, height from floor is within 750mm - 1,000mm.
- ・ It becomes 535mm from a crank stopper to the pillar upper end.



6. Contact

■CycleLocker Inc.

Address: Nagae 17, Hayama-machi, Miura-gun, Kanagawa:

postal code 240-0113

MAIL:info@cyclelocker.net

WEB http://cyclelocker.net

SEP 2016 CS-650BK/CS-650WH/CS-650RD